SUMMIT

FF1843BIFADA



31.5" x 17.75" x 24" (H x W x D)

18" wide ADA compliant built-in undercounter allrefrigerator with a panel-ready door, and digital thermostat

Highlights:

32" height allows installation under lower ADA compliant counters

Just under 18" wide for an easy fit, with a flush back design to save space

Flexible design allows built-in or freestanding use

Product Features:

ADA compliant	32" height is designed to fit under lower ADA compliant counters	
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for use in commercial establishments	
Integrated door frame	Stainless steel door frame accepts full overlay panels for users to create a seamless custom look (panel size: 17 1/2" W x 27 3/4" H; maximum weight: 10 lbs.))	
Automatic defrost	Reduced maintenance with auto defrost system	
Digital thermostat	Electronic controls for precise temperature management.	
Digital display	Temperature readout can be shown in Celsius or Fahrenheit	
LED lighting	Automatically illuminates when the door is open	
Adjustable chrome shelves	Rearrange interior space to accommodate all sizes or remove shelves for simple cleanup	





FF1843BIFADA Specifications:

Height of Cabinet 31.5" (80 cm) Width 17.75" (45 cm) Width with Door Open 18.63" (47 cm) Depth 24.0" (61 cm) Depth with door at 90° 40.0" (102 cm) Capacity 2.7 cu.ft. (76 L) Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 250.0kWh/year			
Width with Door Open 18.63" (47 cm) Depth 24.0" (61 cm) Depth with door at 90° 40.0" (102 cm) Capacity 2.7 cu.ft. (76 L) Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
Depth 24.0" (61 cm) Depth with door at 90° 40.0" (102 cm) Capacity 2.7 cu.ft. (76 L) Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
Depth with door at 90° 40.0" (102 cm) Capacity 2.7 cu.ft. (76 L) Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
Capacity 2.7 cu.ft. (76 L) Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
Defrost Type Automatic Door Panel-Ready Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
DoorPanel-ReadyCabinetBlackUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-S			
Cabinet Black US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S			
US Electrical Safety ETL Canadian Electrical ETL-C Safety Sanitation ETL-S			
Canadian Electrical ETL-C Safety Sanitation ETL-S			
Safety Sanitation ETL-S			
Energy Usage/Year 250 0k\Mb/year			
Energy Osago, real 250.0kWii/year			
Amps 1.1			
Voltage/Frequency 115 V AC/60 Hz			
Weight 90.0 lbs. (41 kg)			
Parts & Labor Warranty 1 Year			
Compressor Warranty 5 Years			
UPC 761101047010			
Refrigerator Features			
Door Swing RHD			
Reversible Factory Reversible			
Shelf Type Chrome			
Shelf Qty 4			
Adjustable Shelves Yes			
Thermostat Type Digital			
Fan Type Interior and Exterior			
Refrigerant Type R600a			
Refrigerant Amount 1.06oz.			
High Side PSI 150.0			
Low Side PSI 50.0			
Level Legs Qty 2			
Interior Light Yes			
Sound Level 33.1 dB			
Dimensions			
Interior Height 23.5" (60 cm)			

Interior Depth	16.75" (43 cm)
Compressor Step Height	4.5" (11 cm)
Compressor Step Width	12.75" (32 cm)
Compressor Step Depth	4.5" (11 cm)

